

Type P16

Features



- ✍ Fully automatic programming control.
- ✍ Models approved by BG plc to EN298 and some ANSI Standards
- ✍ Models available for forced draught and atmospheric burners up to and beyond 60KW

Options include

- ✍ Single Probe.
- ✍ Dual Probe.
- ✍ Slow Spark : Nominal 5HZ spark rate (for use on domestic appliances).
- ✍ Fast Spark : 50HZ spark rate (for use on commercial/industrial heaters etc.).
- ✍ Air pressure switch proving for forced draught (fanned) appliances.
- ✍ Option of electrical reset on lockout (IE control can be reset by switching mains supply switch or resetting thermostat as approved by BG plc).
- ✍ Manual reset on lockout reset by manual interruption of reset circuit. (ie control cannot reset by interrupting mains supply or by cycling of thermostat).

Applications:

- ✍ Domestic boilers.
- ✍ Radiant tube heating.
- ✍ Commercial boilers.
- ✍ Commercial air heaters.
- ✍ Catering appliances.
- ✍ Process heating.
- ✍ Agricultural heaters.
- ✍ Domestic room heaters.

Construction

IP40 housing, dimensions, 140 x 100 x 54 mm,, 10 and 12 way plug in connections

[print](#)

[close window](#)